

Mounting:	recessed
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19	- down diffused with E2 opal
Light output:	down prismatic 2'240lm	- down opal 1'904lm
CCT:	3'000K (4'000K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal life time:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 25W
Voltage:	24VDC
Power supply:	not included


DIMENSIONS & WEIGHT

Dimensions: Length 59x59cm Height 3,5cm Width 5,5cm

Ambient temperature range: -10 / +35°C

Materials:
body: extruded aluminum
cover: pmma OPAL / pmma PRISM

Weight: 1,5 kg



CODES

Rev.A


4037KGAE2 (opal)
4037KGAE19 (prism)



Emme24 recessed corner joint
designed by TI Lighting LAB

Recessed corner joint, length 59x59cm.
DOWN light emission.


<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



CERTIFICATE



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

white/black

CODES

Rev.A


4037KGAE2 (opal)
4037KGAE19 (prism)



Emme24 recessed corner joint
designed by TI Lighting LAB

Recessed corner joint, length 59x59cm.
DOWN light emission.

<input type="checkbox"/>	BV	White
<input checked="" type="checkbox"/>	NE	Black



CERTIFICATE



LIGHT EMISSION

