

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down 24° optic
Light output:	down adjustable 2x360lm
CCT:	3'000K (4'000K on request)
Light source:	Led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	2x3W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

DIMENSIONS & WEIGHT


Dimensions:	Ø10cm H64cm - Spotlights Ø4cm H9cm
Ambient temperature range:	-10 / +35°C
Materials:	body: metal cover: 24° optic
Weight:	2kg



Micro ceiling 2 spotlights
designed by TI Lighting LAB

Ceiling lamp, dimensions Ø10cm H64cm,
with adjustable spotlights Ø3cm H11cm.
Adjustable DOWNLIGHT emission.



NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3039DM

PHASE CUT

Code: not available

STRUCTURE FINISHES


☐ BV white



Micro ceiling 2 spotlights
designed by TI Lighting LAB

Ceiling lamp, dimensions Ø10cm H64cm, with adjustable spotlights Ø3cm H11cm. Adjustable DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

