

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down 24° optic	+ down diffused with E2 opal
Light output:	down adjustable 2x360lm	+ down diffused 1'500lm
CCT:	3'000K (4'000K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	2x3W + 15W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: Ø50cm H54,4cm - Spotlights Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials:
body: metal
cover: 24° optic + pmma OPAL

Weight: 4,5kg




Micro ceiling 2 spotlights + diffused
designed by TI Lighting LAB

Ceiling lamp, dimensions Ø50cm H54,4cm, with adjustable spotlights Ø3cm H11cm and diffused light Ø25cm. Adjustable DOWNLIGHT emission + diffused DOWNLIGHT emission.




Gold/Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3039EDM

PHASE CUT

Code: 3039ET**F**

STRUCTURE FINISHES


☒ NE black
☐ BV white



Micro ceiling 2 spotlights + diffused
designed by TI Lighting LAB

Ceiling lamp, dimensions Ø50cm H54,4cm, with adjustable spotlights Ø3cm H11cm and diffused light Ø25cm. Adjustable DOWNLIGHT emission + diffused DOWNLIGHT emission.

 **ON** Gold/Black



CERTIFICATIONS



LIGHT EMISSION

