

Mounting:	recessed
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down 24° optic
Light output:	down adjustable 1x360lm
CCT:	3'000K (4'000K on request)
Light source:	Led SMD C.R.I.>90
Nominal life time:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	1x3W
Voltage:	220VAC
Power supply:	not included

DIMENSIONS & WEIGHT

Dimensions: Ø10cm H35cm - Spotlight Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials: body: metal
cover: 24° optic

Weight: 1,5kg



CODES

Rev.A


4039A24 (24° optic)



Micro recessed 1 spotlight
designed by TI Lighting LAB

Recessed lamp, dimensions Ø10cm H35cm, with adjustable spotlight Ø3cm H11cm.
DOWN light emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



4039A24 (24° optic)

OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES


on request:
☐ BV white



Micro recessed 1 spotlight
 designed by TI Lighting LAB

Recessed lamp, dimensions Ø10cm
 H35cm, with adjustable spotlight Ø3cm
 H11cm.
 DOWN light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

