

1035DOFE28 (frosted)

<b>Mounting:</b>	pendant
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

<b>Lighting effects:</b>	up with frosted E28
<b>Light output:</b>	up frosted 3'732lm
<b>CCT:</b>	3'000K (4'000K on request)
<b>Light source:</b>	led SMD      C.R.I.>90
<b>Nominal life time:</b>	50'000h      L80B20      (Ta 25°C)

## ELECTRICAL DATA

<b>Wattage:</b>	up 29W
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off driver included inside of the lamp

## DIMENSIONS & WEIGHT

**DimensionS:**      Lenght 168cm    Width 8.5    Height 5.5cm

**Ambient temperature range:**    -10 / +35°C

**Materials:**      body:      extruded aluminum  
                         cover:      pmma FROSTED


**Weight:**      2,5 kg




**Mirò suspension linear module**  
designed by TI Lighting LAB

Suspension linear module, lenght 168cm.  
UP light emission

<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



## CERTIFICATE



1035DOFE28 (frosted)

## OPTIONS

DIMMABLE DALI (Push)

Code:  1035DDME28 (frosted)

## STRUCTURE FINISHES


White/Black



**Mirò suspension linear module**  
designed by TI Lighting LAB

Suspension linear module, lenght 168cm.  
UP light emission

<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



## CERTIFICATE

