

**Mounting:** pendant  
**Environment:** indoor  
**Typical use:** residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

**Lighting effects:** up with frosted E28  
**Light output:** up frosted 9'008lm  
**CCT:** 3'000K (4'000K on request)  
**Light source:** led SMD C.R.I.>90  
**Nominal life time:** 50'000h L80B20 (Ta 25°C)

## ELECTRICAL DATA

**Wattage:** up 70W  
**Voltage:** 220VAC  
**Power supply:** on/off driver included inside of the lamp

## DIMENSIONS & WEIGHT


**DimensionS:** lenght 394cm Width 8.5 Height 5.5cm  
**Ambient temperature range:** -10 / +35°C  
**Materials:** body: extruded aluminum  
cover: pmma FROSTED  
**Weight:** 8 kg




**Mirò suspension linear module**  
designed by TI Lighting LAB

Suspension linear module, lenght 394cm, composed by two 197cm modules.  
UP light emission

- BV White
- NE Black



## CERTIFICATE



1035LOFE28 (frosted)

OPTIONS

DIMMABLE DALI (Push)

Code:  1035LDME28 (frosted)

STRUCTURE FINISHES


White/Black



**Mirò suspension linear module**  
designed by TI Lighting LAB

Suspension linear module, lenght 394cm,  
composed by two 197cm modules.  
UP light emission

- BV White
- NE Black



CERTIFICATE

