

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	up with frosted E28
Light output:	up frosted 13'900lm
CCT:	3'000K (4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal life time:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	up 108W
Voltage:	220VAC
Power supply:	on/off driver included inside of the lamp

DIMENSIONS & WEIGHT

DimensionS: lenght 562cm Width 8.5 Height 5.5cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
 cover: pmma FROSTED


Weight: 11 kg




Mirò suspension linear module
designed by TI Lighting LAB

Suspension linear module, lenght 562cm,
composed by two 281 cm modules.
UP light emission

<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



CERTIFICATE



1035NOFE28 (frosted)

OPTIONS

DIMMABLE DALI (Push)

Code:  1035NDME28 (frosted)

STRUCTURE FINISHES


White/Black



Mirò suspension linear module
designed by TI Lighting LAB

Suspension linear module, lenght 562cm,
composed by two 281 cm modules.
UP light emission

<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



CERTIFICATE

