

Mounting: pendant
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects: up with frosted E28
Light output: up frosted 15'958lm
CCT: 3'000K (4'000K on request)
Light source: led SMD C.R.I.>90
Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: up 124W
Voltage: 220VAC
Power supply: on/off driver included inside of the lamp

DIMENSIONS & WEIGHT

DimensionS: lenght 675cm Width 8.5 Height 5.5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma FROSTED
Weight: 12,5 kg




103500FE28 (frosted)




Mirò suspension linear module
designed by TI Lighting LAB

Suspension linear module, lenght 675cm, composed by two 197cm modules, and one 281cm module.
UP light emission

- BV White
- NE Black



CERTIFICATE



103500FE28 (frosted)

OPTIONS

DIMMABLE DALI (Push)

Code:  10350DME28 (frosted)

STRUCTURE FINISHES


White/Black



Mirò suspension linear module
designed by TI Lighting LAB

Suspension linear module, length 675cm, composed by two 197cm modules, and one 281cm module.
UP light emission

- BV White
- NE Black



CERTIFICATE

