

| | |
|---------------------|---|
| Mounting: | recessed |
| Environment: | outdoor |
| Typical use: | swimming pools, terraces, walkways, saunas, meeting rooms, spas, hotels |

OPTIC

| | | | |
|-------------------|--------------|-----------|-----------|
| Lighting effects: | up 24° optic | | |
| Light output: | up 120lm | | |
| CCT: | 3'000K | | |
| Light source: | Led SMD | C.R.I.>90 | |
| Nominal lifetime: | 50'000h | L80B20 | (Ta 25°C) |

ELECTRICAL DATA

| | |
|----------------------|--------------|
| Wattage: | 1W |
| Voltage: | 350mA - 3VDC |
| Power supply: | not included |

DIMENSIONS & WEIGHT


| | |
|-----------------------------------|---|
| Dimensions: | Ø3,7cm H3,5cm |
| Ambient temperature range: | -10 / +35°C |
| Materials: | body: anodized aluminum cover: 24° optic |
| Weight: | 0,5kg |



Dot recessed spotlight
designed by TI Lighting LAB

Walkable recessed spotlight not carriageable in anodized aluminum and glass, dimensions Ø3,7cm H3,5cm. UP light emission.


 **AL** Aluminum



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

on request:


-



Dot recessed spotlight
designed by TI Lighting LAB

Walkable recessed spotlight not carriageable in anodized aluminum and glass, dimensions Ø3,7cm H3,5cm. UP light emission.

 **AL** Aluminum



CERTIFICATIONS



LIGHT EMISSION

