

<b>Mounting:</b>	recessed
<b>Environment:</b>	outdoor
<b>Typical use:</b>	swimming pools, terraces, walkways, saunas, meeting rooms, spas, hotels

## **OPTIC**

<b>Lighting effects:</b>	radial 24° optic
<b>Light output:</b>	radial 360lm
<b>CCT:</b>	3'000K
<b>Light source:</b>	led SMD      C.R.I.>90
<b>Nominal lifetime:</b>	50'000h      L80B20      (Ta 25°C)

## **ELECTRICAL DATA**

<b>Wattage:</b>	3W
<b>Voltage:</b>	350mA - 9VDC
<b>Power supply:</b>	not included

## **DIMENSIONS & WEIGHT**


<b>Dimensions:</b>	Ø5,6cm H6,2cm
<b>Ambient temperature range:</b>	-10 / +35°C
<b>Materials:</b>	body: anodized aluminum cover: 24° optic
<b>Weight:</b>	1kg



**Dot recessed spotlight**  
designed by TI Lighting LAB

Walkable recessed spotlight not carriageable in anodized aluminum and glass, dimensions Ø5,6cm H6,2cm. RADIAL light emission.


 **AL**      Aluminum



## **CERTIFICATIONS**



## **LIGHT EMISSION**



## OPTIONS

### DIMMABLE DALI (Push)

Code:  not available

### PHASE CUT

Code: not available

### STRUCTURE FINISHES

on request:


-



**Dot recessed spotlight**  
designed by TI Lighting LAB

Walkable recessed spotlight not carriageable in anodized aluminum and glass, dimensions Ø5,6cm H6,2cm. RADIAL light emission.

 **AL** Aluminum



## CERTIFICATIONS



## LIGHT EMISSION

