

Mounting:	ceiling
Environment:	outdoor
Typical use:	residential, hotels, swimming pools, spas

OPTIC


Lighting effects:	diffused down with E2 opal		
Light source:	down 2'150lm		
CCT:	2'700K (3'000K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal life time:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	down 48W
Voltage:	24VDC
Power supply:	not included

DIMENSIONS & WEIGHT


Dimensions:	Ø82cm Section H3x1,5cm	
Ambient temperature range:	-10 / +35°C	
Materials:	body:	extruded aluminum
	cover:	pmma OPAL
Weight:	3 kg	



Leggera ceiling Ø82cm
designed by TI Lighting LAB

Ceiling lamp with Ø82cm dimensions in painted aluminum.
DOWNLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES


☐ BV white



Leggera ceiling Ø82cm
designed by TI Lighting LAB

Ceiling lamp with Ø82cm dimensions in painted aluminum.
DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

