

Mounting: wall
Environment: outdoor
Typical use: arcades, terraces, gardens

OPTIC

Lighting effects: down optic 24°
Light output: down 815lm
CCT: 3'000K
Light source: Led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 8W
Voltage: 220VAC
Power supply: on/off incorporated


DIMENSIONS & WEIGHT

Dimensions: Length 11,6cm Height 10,9cm Ø7,3cm

Ambient temperature range: -10 / +35°C

Materials: body: aluminum
 diffusore: 24° optic


Weight: 1,5kg



Flip wall
 designed by TI Lighting LAB

Adjustable wall spotlight with two degrees of freedom. Body in powder-coated aluminum and glass, builtin power supply. Adjustable DOWNLIGHT emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

on request:

-




Flip wall

designed by TI Lighting LAB

Adjustable wall spotlight with two degrees of freedom. Body in powder-coated aluminum and glass, built-in power supply. Adjustable DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

