

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	up+down diffused with E2 opal		
Light output:	up+down diffused 6'500lm		
CCT:	3'000K (4'000K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	up 63W + down 63W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

WEIGHT & DIMENSIONS


Dimensions:	length 281cm section Height 10cm Width 5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL	
Weight:	4,5 kg		



Mirò wall
designed by TI Lighting LAB

Wall linear lamp, length 281cm.
UP+DOWN light emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



2030HOFE2 (opal)


OPTIONS

DIMMABLE DALI (Push)

Code:  2030HDME2 (opal)

STRUCTURE FINISHES


on request:
☐ BV white
☐ SO brushed aluminum



Mirò wall
 designed by TI Lighting LAB

Wall linear lamp, lenght 281cm.
 UP+DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

