

<b>Mounting:</b>	wall
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

<b>Lighting effects:</b>	up+down diffused with E2 opal		
<b>Light output:</b>	up+down diffused 18'140lm		
<b>CCT:</b>	3'000K (4'000K on request)		
<b>Light source:</b>	led SMD	C.R.I.>90	
<b>Nominal lifetime:</b>	50'000h	L80B20	(Ta 25°C)

## ELECTRICAL DATA

<b>Wattage:</b>	up 175W + down 175W
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off included inside the lamp

## WEIGHT & DIMENSIONS

Dimensions:	length 787cm section Height 10cm Width 5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL / pmma PRISM	
Weight:	14,5 kg		



## CODES

Rev.A


2030POFE2 (opal)



**Mirò wall**  
designed by TI Lighting LAB

Wall linear lamp, length 787cm, composed by two 253cm modules and one 281cm module.  
UP+DOWN light emission.


■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



2030POFE2 (opal)


## OPTIONS

DIMMABLE DALI (Push)

Code:  2030PDME2 (opal)

## STRUCTURE FINISHES


- on request:
- ☐ BV white
  - ☐ SO brushed aluminum



**Mirò wall**  
designed by TI Lighting LAB

Wall linear lamp, lenght 787cm, composed by two 253cm modules and one 281cm module.  
UP+DOWN light emission.

 NE Black



## CERTIFICATIONS



## LIGHT EMISSION

