

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	up+down diffuse with E2 opal		
Light output:	up+down diffused 23'280lm		
CCT:	3'000K (4'000K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	up 224W + down 224W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

WEIGHT & DIMENSIONS

Dimensions: lenght 1'012cm section Height 10cm Width 5cm

Ambient temperature range: -10 / +35°C

Materials:
body: extruded aluminum
cover: pmma OPAL / pmma PRISM

Weight: 18 kg



CODES

Rev.A


2030RFE2 (opal)



Mirò wall
designed by TI Lighting LAB

Wall linear lamp, lenght 1'012cm,
composed by four 253cm modules.
UP+DOWN light emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



2030RFE2 (opal)


OPTIONS

DIMMABLE DALI (Push)

Code:  2030RDME2 (opal)

STRUCTURE FINISHES

- on request:
- ☐ BV white
 - ☒ SO brushed aluminum




Mirò wall

designed by TI Lighting LAB

Wall linear lamp, lenght 1'012cm,
composed by four 253cm modules.
UP+DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

