

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down 24° optic
Light output:	down adjustable 2x680lm
CCT:	3'000K (4'000K on request)
Light source:	Led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	2x7W
Voltage:	220VAC
Power supply:	on/off included inside the lamp


DIMENSIONS & WEIGHT

Dimensions: L20x11cm H4cm - Spotlights Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials: body: metal
cover: 24° optic

Weight: 2kg




Tablet Square ceiling 2 spotlights
designed by TI Lighting LAB

Ceiling lamp, base dimensions L20x11cm H4cm, with adjustable spotlights Ø4cm H9cm.
Adjustable DOWNLIGHT emission.



NO


Black/Gold



CERTIFICATIONS



LIGHT EMISSION



OPTIONS


DIMMABLE DALI (Push)

Code:  3044NDM

PHASE CUT

Code: 3044NTF


STRUCTURE FINISHES


 BV white
 NE black



Tablet Square ceiling 2 spotlights
designed by TI Lighting LAB

Ceiling lamp, base dimensions L20x11cm
H4cm, with adjustable spotlights Ø4cm
H9cm.
Adjustable DOWNLIGHT emission.

 NO Black/Gold



CERTIFICATIONS



LIGHT EMISSION

