

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down diffused with E2 opal	+ down 24° optic
Light output:	down diffused 2'860lm	+ down adjustable 2x680lm
CCT:	3'000K (4'000K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	25W + 2x7W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: Length 60cm Width 14,5cm Height 3,5cm - Spotlights Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials:
body: metal
cover: pmma OPAL + 24° optic

Weight: 3kg




Tablet Round ceiling 2 spotlights + diffused
designed by TI Lighting LAB

Ceiling lamp, dimensions L60x14,5cm
H3,5cm, with adjustable spotlights Ø4cm
H9cm.
Downlight + adjustable light emission.



NO


Black/Gold



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3044SDM

PHASE CUT

Code: 3044STF

STRUCTURE FINISHES

 BV white
 NE black



Tablet Round ceiling 2 spotlights + diffused
designed by TI Lighting LAB


Ceiling lamp, dimensions L60x14,5cm
H3,5cm, with adjustable spotlights Ø4cm
H9cm.

Downlight + adjustable light emission.



NO

Black/Gold



CERTIFICATIONS



LIGHT EMISSION

