

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down diffused with E2 opal
Light output:	down diffused 2'490lm
CCT:	3'000K (2'700K on request)
Light source:	led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 34W
Voltage:	220VAC
Power supply:	on/off incorporated

WEIGHT&DIMENSIONS


Dimensions:	Length 135cm Height 50cm Section H.4x3,5cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL
Weight:	1,5 kg



Edge wall
designed by TI Lighting LAB

Wall lamp, length 135cm Height 50cm, with a 90° corner. Integrated power supply. DOWNLIGHT emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  2028GOFDM

PHASE CUT

Code: not available

STRUCTURE FINISHES

- ☐ BV white
- ☐ TO dove grey
- ☐ RU rust
- ☐ GV grey




Edge wall

designed by TI Lighting LAB

Wall lamp, length 135cm Height 50cm, with a 90° corner. Integrated power supply. DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

