

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	down diffused with frosted E28		
Light output:	down diffused 3'500lm		
CCT:	3'000K		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA


Wattage:	down 43W
Voltage:	220VAC
Power supply:	(on/off) incorporated

WEIGHT & DIMENSIONS

Dimensions:	L.50x50cm H9cm		
Temperature ambient range:	-10 / +35°C		
Materials:	body:	aluminum	
	cover:	pmma FROSTED	
Weight:	2,5 kg		




3009NTE28 (frosted)



Oki triple ceiling
designed by TI Lighting LAB

Ceiling lamp in aluminum, dimensions
L50x50cm H9cm.
DOWN light emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS






DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

	BV	white
	TO	dove grey
	RU	rust
	GV	grey
	SO	brushed aluminum




Oki triple ceiling

designed by TI Lighting LAB

Ceiling lamp in aluminum, dimensions L50x50cm H9cm.
DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

