

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	down optic 24° - up satinated E28
Light output:	down 5x680lm - up 2'390lm
CCT:	3'000K (4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal life time:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down spotlights 5x7W - up 18W
Voltage:	220VAC
Power supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT


Dimensions:	Length 225cm Height 8,5cm Width 5,5cm - Spotlights Ø4cm H9cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: optic 24° / pmma FROSTED
Weight:	4 kg



CODES

Rev.B


1030S6OF24 (Optic 24°)



Mirò suspension + adjustable spotlights
designed by TI Lighting LAB

Suspension joint lamp with adjustable spotlights, length 225cm.
DOWN light emission.



 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



24°+E28

1030S6OF24 (Optic 24°)


OPTIONS

DIMMABLE DALI (Push)

Code:  1030S6DM24


STRUCTURE FINISHES


on request:
☐ BV White



Mirò suspension + adjustable spotlights
designed by TI Lighting LAB

Suspension joint lamp with adjustable spotlights, length 225cm.
DOWN light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

