

<b>Mounting:</b>	ceiling
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

<b>Lighting effects:</b>	optic 24°
<b>Light output:</b>	5x680lm
<b>CCT:</b>	3'000K (4'000K on request)
<b>Light source:</b>	led SMD      C.R.I.>90
<b>Nominal life time:</b>	50'000h      L80B20      (Ta 25°C)

## ELECTRICAL DATA

<b>Wattage:</b>	spotlights 5x7W
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off driver included inside the lamp


## DIMENSIONS & WEIGHT

**Dimensions:** Length 197cm Height 8,5cm Width 5,5cm - Spotlights Ø4cm H9cm

**Ambient temperature range:** -10 / +35°C

**Materials:**  
body: extruded aluminum  
cover: optic 24°


**Weight:** 3,5 kg



## CODES

Rev.B


3030S5OF24 (Optic 24°)



**Mirò ceiling + adjustable spotlights**  
designed by TI Lighting LAB

Ceiling joint lamp with adjustable spotlights,  
length 197cm.  
DOWN light emission.


 **NE**      Black



## CERTIFICATIONS



## LIGHT EMISSION




## OPTIONS

DIMMABLE DALI (Push)

Code:  3030S5DM24


## STRUCTURE FINISHES


on request:  
☐ BV White



**Mirò ceiling + adjustable spotlights**  
designed by TI Lighting LAB

Ceiling joint lamp with adjustable spotlights,  
length 197cm.  
DOWN light emission.

 NE Black



## CERTIFICATIONS



## LIGHT EMISSION

