

<b>Mounting:</b>	ceiling
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

<b>Lighting effects:</b>	down ugr with prismatic E19	- down diffuse with E2 opal
<b>Light output:</b>	down prismatic 16'860lm	- down opal 14'331lm
<b>CCT:</b>	3'000K (4'000K on request)	
<b>Light source:</b>	Led SMD	C.R.I.>90
<b>Nominal lifetime:</b>	50'000h	L80B20 (Ta 25°C)

## ELECTRICAL DATA

<b>Wattage:</b>	down 185W
<b>Voltage:</b>	24VDC
<b>Power supply:</b>	not included

## DIMENSIONS & WEIGHT

**Dimensions:** Length 843cm Height 6,5cm Width 4,3cm

**Ambient temperature range:** -10 / +35°C

**Materials:**  
body: extruded aluminum  
cover: pmma OPAL / pmma PRISM

**Weight:** 15,5 kg




3037QE2 (opal)  
3037QE19 (prism)



**Emme24 ceiling**  
designed by TI Lighting LAB

Ceiling linear lamp, length 843cm, composed by three 281cm modules. DOWN light emission.


□ BV	White
■ NE	Black



## CERTIFICATIONS



## LIGHT EMISSION



3037QE2 (opal)  
3037QE19 (prism)

## OPTIONS

### DIMMABLE DALI (Push)

Code:  not available

### PHASE CUT

Code: not available

### STRUCTURE FINISHES

white/black




### Emme24 ceiling

designed by TI Lighting LAB

Ceiling linear lamp, length 843cm, composed by three 281cm modules. DOWN light emission.

<input type="checkbox"/>	BV	White
<input type="checkbox"/>	NE	Black



## CERTIFICATIONS



## LIGHT EMISSION

