

**Mounting:** ceiling

**Environment:** indoor

**Typical use:** residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

**Lighting effects:** down ugr with prismatic E19 - down diffuse with E2 opal

**Light output:** down prismatic 20'240lm - down opal 17'204lm

**CCT:** 3'000K (4'000K on request)

**Light source:** led SMD C.R.I.>90

**Nominal lifetime:** 50'000h L80B20 (Ta 25°C)

## ELECTRICAL DATA

**Wattage:** down 223W

**Voltage:** 24VDC

**Power supply:** not included

## DIMENSIONS & WEIGHT

**Dimensions:** length 1'012cm Height 6,5cm Width 4,3cm


**Ambient temperature range:** -10 / +35°C

**Materials:** body: extruded aluminum  
cover: pmma OPAL / pmma PRISM

**Weight:** 18 kg




3037RE2 (opal)  
3037RE19 (prism)



**Emme24 ceiling**  
designed by TI Lighting LAB

Ceiling linear lamp, length 843cm, composed by four 253cm modules. DOWN light emission.


□ BV White  
■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



3037RE2 (opal)  
3037RE19 (prism)

OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES


white/black



**Emme24 ceiling**  
designed by TI Lighting LAB

Ceiling linear lamp, length 843cm, composed by four 253cm modules. DOWN light emission.

- BV White
- NE Black



CERTIFICATIONS



LIGHT EMISSION

