

**Mounting:** ceiling  
**Environment:** indoor  
**Typical use:** residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

**Lighting effects:** down ugr with prismatic E19 - down diffused with E2 opal  
**Light output:** down prismatic 2'240lm - down opal 1'904lm  
**CCT:** 3'000K (4'000K on request)  
**Light source:** led SMD C.R.I.>90  
**Nominal lifetime:** 50'000h L80B20 (Ta 25°C)

## ELECTRICAL DATA

**Wattage:** down 25W  
**Voltage:** 24VDC  
**Power supply:** not included

## DIMENSIONS & WEIGHT


**Dimensions:** length 59x59cm Height 6,5cm Width 4,3cm

**Ambiente temperature range:** -10 / +35°C

**Materials:** body: extruded aluminum  
 cover: pmma OPAL / pmma PRISM

**Weight:** 1,5 kg



3037KGAE2 (opal)  
 3037KGAE19 (prism)



**Emme24 ceiling corner joint**  
 designed by TI Lighting LAB

Ceiling corner joint, length 59x59cm.  
 DOWN light emission.


□ BV White  
 ■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



3037KGAE2 (opal)  
3037KGAE19 (prism)

OPTIONS

DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES


white/black



**Emme24 ceiling corner joint**  
designed by TI Lighting LAB

Ceiling corner joint, length 59x59cm.  
DOWN light emission.

- BV White
- NE Black



CERTIFICATIONS



LIGHT EMISSION

