

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused indirect with frosted E28		
Light output:	indirect 1'900lm		
CCT:	3'000K (2'700K on request)		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	15W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT

Dimensions: Ø35cm distance from the wall 10cm

Ambient temperature range: -10 / +35°C

Materials: body: aluminum
cover: pmma FROSTED


Weight: 2kg



Velata wall Ø35cm
designed by TI Lighting LAB

Wall lamp, diameter 35cm, in powder coated aluminum. Built-in power supply. Diffused INDIRECT light emission.


☐ BV White



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  2038ADM

PHASE CUT

Code: 2038ATF

STRUCTURE FINISHES


	NE	black
	TO	dove grey
	RV	painted copper
	BR	painted bronze
	OV	painted gold



Velata wall Ø35cm
designed by TI Lighting LAB

Wall lamp, diameter 35cm, in powder coated aluminum. Built-in power supply. Diffused INDIRECT light emission.

 **BV** White



CERTIFICATIONS



LIGHT EMISSION

