

| | |
|---------------------|---|
| Mounting: | ceiling |
| Environment: | indoor |
| Typical use: | residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops |

OPTIC

| | |
|--------------------------|----------------------------|
| Lighting effects: | down 24° optic |
| Light output: | down adjustable 4x680lm |
| CCT: | 3'000K (4'000K on request) |
| Light source: | Led SMD C.R.I.>90 |
| Nominal lifetime: | 50'000h L80B20 (Ta 25°C) |

ELECTRICAL DATA

| | |
|----------------------|---------------------------------|
| Wattage: | 4x7W |
| Voltage: | 220VAC |
| Power supply: | on/off included inside the lamp |

WEIGHT & DIMENSIONS

Dimensions: L28x28cm H4,8cm - Spotlights Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials: body: metal
cover: 24° optic

Weight: 3kg




Tablet Square ceiling 4 spotlights
designed by TI Lighting LAB

Ceiling lamp, base dimensions L28x28cm
H4,8cm, with adjustable spotlights Ø4cm
H9cm.
Adjustable DOWNLIGHT emission.



NO



Black/Gold



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3044FDM

PHASE CUT

Code: not available

STRUCTURE FINISHES


 BV white
 NE black



Tablet Square ceiling 4 spotlights
designed by TI Lighting LAB

Ceiling lamp, base dimensions L28x28cm
H4,8cm, with adjustable spotlights Ø4cm
H9cm.
Adjustable DOWNLIGHT emission.

 NO Black/Gold



CERTIFICATIONS



LIGHT EMISSION

