

Mounting: wall
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC



Lighting effects: diffused frontal with E2 opal
Light output: frontal 1'050lm
CCT: 3'000K (2'700K or 4'000K on request)
Light source: Led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 25W
Voltage: 220VAC
Power supply: on/off incorporated

DIMENSIONS & WEIGHT


Dimensions: Ø45cm section H3x1,5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL
Weight: 1,5kg



Leggera wall Ø45cm
designed by TI Lighting LAB

Wall lamp with dimensions Ø45cm in painted aluminum.
FRONTAL light emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  2032CDM

PHASE CUT

Code: 2032CTF

STRUCTURE FINISHES


-  BV white
-  OV painted gold
-  RV painted copper
-  BR painted bronze



Leggera wall Ø45cm
designed by TI Lighting LAB

Wall lamp with dimensions Ø45cm in painted aluminum.
FRONTAL light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

