

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTICS

Lighting effects:	up diffused with E28 frosted		
Light output:	up diffused 4'050lm		
CCT:	3'000K (2'700K su richiesta)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELETTRICHE

Wattage:	36W
Voltage:	220VAC
Power supply:	on/off incorporated

WEIGHT & DIMENSIONS

Dimensions: Length 124cm Width 20cm Height 4cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma frosted


Weight: 3kg



RIFLESSA UP suspension
designed by TI Lighting LAB

Linear suspension lamp, length 124cm, with integrated power supply unit and indirect diffuse light source. Aluminum finishing and frosted pmma diffuser.
UP light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



1052BOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1052BDM

PHASE CUT

Codice: not available

BLUETOOTH

Code: 1052BBT


STRUCTURE FINISHES


-  BV white
-  TO dove grey
-  RU painted rust
-  RV painted copper
-  BR painted bronze
-  OV painted gold
-  SO brushed aluminum



RIFLESSA UP suspension
designed by TI Lighting LAB

Linear suspension lamp, length 124cm, with integrated power supply unit and indirect diffuse light source. Aluminum finishing and frosted pmma diffuser.
UP light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

