

| | |
|--------------|---|
| Mounting: | pendant |
| Environment: | indoor |
| Typical use: | residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops |

OPTICS

| | | | |
|-------------------|------------------------------|-----------|-----------|
| Lighting effects: | up diffused with E28 frosted | | |
| Light output: | up diffused 7'050lm | | |
| CCT: | 3'000K (2'700K su richiesta) | | |
| Light source: | led SMD | C.R.I.>90 | |
| Nominal lifetime: | 50'000h | l80B20 | (Ta 25°C) |

ELETTRICHE

| | |
|---------------|---------------------|
| Wattage: | 63W |
| Voltage: | 220VAC |
| Power supply: | on/off incorporated |

WEIGHT & DIMENSIONS

Dimensions: Length 208cm Width 20cm Height 4cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma frosted


Weight: 5kg



RIFLESSA UP suspension
designed by TI Lighting LAB

Linear suspension lamp, length 208cm, with integrated power supply unit and indirect diffuse light source. Aluminum finishing and frosted pmma diffuser.
UP light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  1052EDM

PHASE CUT

Codice: not available

BLUETOOTH

Code: 1052EBT


STRUCTURE FINISHES


-  BV white
-  TO dove grey
-  RU painted rust
-  RV painted copper
-  BR painted bronze
-  OV painted gold
-  SO brushed aluminum



RIFLESSA UP suspension
designed by TI Lighting LAB

Linear suspension lamp, length 208cm, with integrated power supply unit and indirect diffuse light source. Aluminum finishing and frosted pmma diffuser.
UP light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

