

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTICS

Lighting effects:	up diffused with E28 frosted	+ down ugr with 55° optic
Light output:	up diffused 4'050lm	+ down ugr 1'000lm
CCT:	3'000K (2'700K su richiesta)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELETTRICHE

Wattage:	up 36W + down 7,5W
Voltage:	220VAC
Power supply:	on/off incorporated

WEIGHT & DIMENSIONS

Dimensions: Length 124cm Width 20cm Height 4cm

Ambient temperature range: -10 / +35°C

Materials:
body: extruded aluminum
cover: pmma frosted/55° optic

Weight: 3kg




1053BOF



RIFLESSA DARK suspension
designed by TI Lighting LAB

Double-light source suspension lamp, length 124cm, the main light source is indirect and diffused. The secondary darklight-source is direct with glare reduction. The power supply is included. Aluminum finishing and frosted pmma diffuser.
UP main light emission + DOWN darklight secondary light emission.


 **TO** Dove grey



CERTIFICATIONS



LIGHT EMISSION



1053BOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1053HDM

PHASE CUT

Codice: not available

BLUETOOTH

Code: 1053HBT

STRUCTURE FINISHES


	BV	white
	NE	black
	RU	painted rust
	RV	painted copper
	BR	painted bronze
	OV	painted gold
	SO	brushed aluminum



RIFLESSA DARK suspension
designed by TI Lighting LAB

Double-light source suspension lamp, length 124cm, the main light source is indirect and diffused. The secondary darklight-source is direct with glare reduction. The power supply is included. Aluminum finishing and frosted pmma diffuser.
UP main light emission + DOWN darklight secondary light emission.

 TO Dove grey



CERTIFICATIONS



LIGHT EMISSION

