

Mounting: pendant
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTICS

Lighting effects: up diffused with E28 frosted + down 24° optic
Light output: up diffused 7'050lm + down adjustable 2x680lm
CCT: 3'000K (2'700K su richiesta)
Light source: led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELETTRICHE

Wattage: up 63W + down 2x7W
Voltage: 220VAC
Power supply: on/off incorporated

WEIGHT & DIMENSIONS

Dimensions: Structure: Length 208cm Width 20cm Height 4cm
 Spotlight: Height 9cm Ø4cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
 cover: pmma frosted


Weight: 5kg



RIFLESSA S-POT suspension
 designed by TI Lighting LAB

Linear bi-emission suspension lamp, length 208cm, the main light source is indirect and diffused. Secondary concentrated light-sources is also adjustable. The power supply is included. Aluminum finished and frosted pmma diffuser.
 UP+DOWN light emission.



ON Oro verniciato/Nero



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  1054EDM

PHASE CUT

Codice: not available

BLUETOOTH

Code: 1054EBT

STRUCTURE FINISHES


-  BB white/white
-  NN black/black
-  TN dove grey/black
-  RN painted copper/black
-  BN painted bronze/black
-  SN brushed aluminum/black



RIFLESSA S-POT suspension
designed by TI Lighting LAB

Linear bi-emission suspension lamp, length 208cm, the main light source is indirect and diffused. Secondary concentrated light-sources is also adjustable. The power supply is included. Aluminum finished and frosted pmma diffuser.
UP+DOWN light emission.

 **ON** Oro verniciato/Nero



CERTIFICATIONS



LIGHT EMISSION

