

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTICS

Lighting effects:	up diffused with E2 opal		
Light output:	up diffused 1'900lm		
CCT:	3'000K (2'700K su richiesta)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELETTRICHE

Wattage:	15W
Voltage:	220VAC
Power supply:	on/off incorporated

WEIGHT & DIMENSIONS

Dimensions: Length 20cm Width 20cm Height 4cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma OPAL


Weight: 0,5kg



RIFLESSA wall
designed by TI Lighting LAB

Linear wall lamp, length 20cm, with reflected light emission. Built-in power supply; painted aluminum structure. UP light emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



2052AOF

OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Codice: 2052ATF

BLUETOOTH

Code: not available

STRUCTURE FINISHES

-  BV white
-  TO dove grey
-  RV painted copper
-  BR painted bronze
-  OV painted gold




RIFLESSA wall

designed by TI Lighting LAB

Linear wall lamp, length 20cm, with reflected light emission. Built-in power supply; painted aluminum structure. UP light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

