

<b>Mounting:</b>	wall
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

## OPTICS

<b>Lighting effects:</b>	up diffused with E2 opal	+ down diffused with E2 opal
<b>Light output:</b>	up diffused 1'900lm	+ down diffused 800lm
<b>CCT:</b>	3'000K (2'700K su richiesta)	
<b>Light source:</b>	led SMD	C.R.I.>90
<b>Nominal lifetime:</b>	50'000h	L80B20 (Ta 25°C)

## ELETTRICHE

<b>Wattage:</b>	up 23W + down 9W
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off incorporated

## WEIGHT & DIMENSIONS

**Dimensions:** Length 45cm Width 20cm Height 4cm

**Ambient temperature range:** -10 / +35°C

**Materials:**  
body: extruded aluminum  
cover: pmma OPAL


**Weight:** 1,5kg



**RIFLESSA wall**  
designed by TI Lighting LAB

Linear wall lamp, length 20cm, with reflected light emission. Built-in power supply; painted aluminum structure.  
UP light emission.


 **NE** Black



## CERTIFICATIONS



## LIGHT EMISSION



## OPTIONS

### DIMMABLE DALI (Push)

Code:  2052DDM

### PHASE CUT

Codice: not available

### BLUETOOTH

Code: not available

## STRUCTURE FINISHES

-  BV white
-  TO dove grey
-  RV painted copper
-  BR painted bronze
-  OV painted gold




### RIFLESSA wall

designed by TI Lighting LAB

Linear wall lamp, length 20cm, with reflected light emission. Built-in power supply; painted aluminum structure.  
UP light emission.

 NE Black



## CERTIFICATIONS



## LIGHT EMISSION

