

Mounting: floor
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTICS

Lighting effects: indirect with E28 frosted
Light output: indirect diffused 4'500lm
CCT: 3'000K (2'700K on request)
Light source: led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 37W
Voltage: 220VAC
Power supply: dimmable included incorporated

WEIGHT & DIMENSIONS


Dimensions: Height 180cm Width 20cm Base 35x35cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma FROSTED
Weight: 5kg



RIFLESSA floor
designed by TI Lighting LAB

Linear floor lamp, height 180cm, with indirect light emission. Built-in power supply, painted aluminum structure and satin pmma diffuser.
INDIRECT light emission.


 OV Painted gold



CERTIFICATIONS



LIGHT EMISSION



5052ADM

OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

BLUETOOTH

Code: 5052ABT

STRUCTURE FINISHES


-  BV white
-  NE black
-  TO dove grey
-  RV painted copper
-  BR painted bronze



RIFLESSA floor
designed by TI Lighting LAB

Linear floor lamp, height 180cm, with indirect light emission. Built-in power supply, painted aluminum structure and satin pmma diffuser.
INDIRECT light emission.

 OV Painted gold



CERTIFICATIONS



LIGHT EMISSION

