

Mounting:	recessed
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OTTICHE

Lighting effects:	down 24° optic
Light output:	down concentrated 1'300lm
CCT:	3'000K
Light source:	Led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 13W
Voltage:	350mA - 36V
Power supply:	remotely not included

DIMENSIONS & WEIGHT

Dimensions:	L.9,5x9,5cm H.11cm
Ambient temperature range:	-10 / +35°C
Materials:	structure: aluminum cover: 24° optic
Weight:	0,5 kg




SIDE

designed by TI Lighting LAB

Recessed spotlight with asymmetric focused light source. Squared shape in powder coated aluminum. Remote power supply not included.

DOWNLIGHT emission.


☐ BV White



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

on request:
not available




SIDE

designed by TI Lighting LAB

Recessed spotlight with asymmetric focused light source. Squared shape in powder coated aluminum. Remote power supply not included.
DOWN light emission.

☐ BV White



CERTIFICATIONS



LIGHT EMISSION

