

Mounting: recessed
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OTTICHE

Lighting effects: down 24° optic
Light output: down concentrated 1'300lm
CCT: 3'000K
Light source: led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 13W
Voltage: 350mA - 36V
Power supply: remotely not included

DIMENSIONS & WEIGHT

Dimensions: Ø9cm H.10,5cm
Ambient temperature range: -10 / +35°C
Materials: structure: aluminum
cover: 24° optic
Weight: 0,5 kg




SIDE

designed by TI Lighting LAB

Recessed spotlight with asymmetric focused light source. Circular shape in powder coated aluminum. Remote power supply not included.

DOWNLIGHT emission.


BV White



CERTIFICATIONS



LIGHT EMISSION



4057B

OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

on request:
not available




SIDE

designed by TI Lighting LAB

Recessed spotlight with asymmetric focused light source. Circular shape in powder coated aluminum. Remote power supply not included. DOWN light emission.

BV White



CERTIFICATIONS



LIGHT EMISSION

