

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	diffused down with E2 opal		
Light output:	down 2'600lm		
CCT:	3'000K		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	l80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	26W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT


Dimensions:	Ø18,5cm Height 6,5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	metal	
	cover:	pmma OPAL	
Weight:	1,5kg		



S-POT ceiling
designed by TI Lighting LAB

Ceiling lamp with dimensions Ø18,5cm H6,5cm, with LED light source. Power supply included.
DOWNLIGHT emission.


☐ BV White



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3018GDM

PHASE CUT

Code: 3018GTF

STRUCTURE FINISHES

on request:
not available




S-POT ceiling

designed by TI Lighting LAB

Ceiling lamp with dimensions Ø18,5cm H6,5cm, with LED light source. Power supply included.

DOWNLIGHT emission.

☐ BV White



CERTIFICATIONS



LIGHT EMISSION

