

<b>Mounting:</b>	ceiling
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## **OPTIC**


<b>Lighting effects:</b>	down accent with prismatic E19 down diffused with E2 opal
<b>Light output:</b>	down 1'190lm (E19) down 1'011lm (E2)
<b>CCT:</b>	3'000K (2'700K or 4'000K on request)
<b>Light source:</b>	led SMD C.R.I.>90
<b>Nominal lifetime:</b>	50'000h L80B20 (Ta 25°C)

## **ELECTRICAL DATA**

<b>Wattage:</b>	down 9W
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off incorporated

## **DIMENSIONS & WEIGHT**


<b>Dimensions:</b>	Length 60cm section H.6,5x4,3cm
<b>Ambient temperature range:</b>	-10 / +35°C
<b>Materials:</b>	body: extruded aluminum cover: pmma PRISM/pmma OPAL
<b>Weight:</b>	1 kg



**M-ECO ceiling**  
designed by TI Lighting LAB

Linear ceiling led lamp, length 60cm, with prismatic or polycarbonate opal diffuser. Integrated power supply. DOWNLIGHT emission.


☐ BV Bianco verniciato



## **CERTIFICATIONS**



## **LIGHT EMISSION**



## OPTIONS

### DIMMABLE DALI (Push)

Code:  not available





### PHASE CUT

Code: 3058UTF

### EMERGENCY

Code: not available

## STRUCTURE FINISHES

	NE	black
	TO	dove grey
	RU	rust
	GV	grey




### M-ECO ceiling

designed by TI Lighting LAB

Linear ceiling led lamp, length 60cm, with prismatic or polycarbonate opal diffuser. Integrated power supply. DOWNLIGHT emission.

☐ BV Bianco verniciato



## CERTIFICATIONS



## LIGHT EMISSION

