

Mounting:	track
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	accent down with prismatic E19 diffused down with E2 opal
Light output:	down 2'380lm (E19) down 2'023lm (E2)
CCT:	3'000K (2'700K or 4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 18W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT


Dimensions:	Length 112cm section H.6,5x4,3cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma PRISM/pmma OPAL
Weight:	1,5 kg



M-ECO track
designed by TI Lighting LAB

Linear led lamp designed for electrified track, length 112cm, with prismatic or polycarbonate opal diffuser. Integrated power supply.
DOWNLIGHT emission.


☐ BV Bianco verniciato



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  T058BDM





PHASE CUT

Code: not available

EMERGENCY

Code: T058BOFEM

STRUCTURE FINISHES

	NE	black
	TO	dove grey
	RU	rust
	GV	grey




M-ECO track

designed by TI Lighting LAB

Linear led lamp designed for electrified track, length 112cm, with prismatic or polycarbonate opal diffuser. Integrated power supply.

DOWNLIGHT emission.

☐ BV Bianco verniciato



CERTIFICATIONS



LIGHT EMISSION

