

Mounting: track
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: down accent with prismatic E19
down diffused with E2 opal

Light output: down 2'975lm (E19)
down 2'528lm (E2)

CCT: 3'000K (2'700K or 4'000K on request)

Light source: led SMD C.R.I.>90

Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 22W
Voltage: 220VAC
Power supply: on/off incorporated

DIMENSIONS & WEIGHT

Dimensions: Length 140cm section H.6,5x4,3cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma PRISM/pmma OPAL


Weight: 2 kg



M-ECO track
designed by TI Lighting LAB

Linear led lamp designed for electrified track, length 140cm, with prismatic or polycarbonate opal diffuser. Integrated power supply.
DOWNLIGHT emission.


BV Bianco verniciato



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  T058CDM

PHASE CUT

Code: not available

EMERGENCY

Code: T058COFEM

STRUCTURE FINISHES

-  NE black
-  TO dove grey
-  RU rust
-  GV grey




M-ECO track

designed by TI Lighting LAB

Linear led lamp designed for electrified track, length 140cm, with prismatic or polycarbonate opal diffuser. Integrated power supply.
DOWNLIGHT emission.

 BV Bianco verniciato



CERTIFICATIONS



LIGHT EMISSION

