

Mounting:	wall
Environment:	outdoor
Typical use:	arcades, terraces, gardens

OPTIC

Lighting effects:	down optic 24°		
Light output:	adjustable down 815lm		
CCT:	3'000K		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	I80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	7W
Voltage:	24VDC - 350mA
Power supply:	not included

DIMENSIONS & WEIGHT

Dimensions: Height 9cm 5Øcm - Ground stake H.60/100cm

Ambient temperature range: -10 / +35°C

Materials: body: aluminum
diffusore: 24° optic

Weight: 0,5kg




Flip wall

designed by TI Lighting LAB

System of modular outdoor low voltage spotlights on a ground stake. Remotely 24VDC power supply not included. Adjustable DOWNLIGHT emission.



 NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

on request:

-




Flip wall

designed by TI Lighting LAB

System of modular outdoor low voltage spotlights on a ground stake. Remotely 24VDC power supply not included. Adjustable DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

