

<b>Mounting:</b>	ceiling
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

<b>Lighting effects:</b>	diffused down with E2 opal		
<b>Light source:</b>	down 2'480lm		
<b>CCT:</b>	2'700K (3'000K on request)		
<b>Light source:</b>	led SMD	C.R.I.>90	
<b>Nominal life time:</b>	50'000h	L80B20	(Ta 25°C)

## ELECTRICAL DATA

<b>Wattage:</b>	down 60W
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off driver included inside the lamp

## DIMENSIONS & WEIGHT

**Dimensions:** Ø45cm + Ø65cm Height 32cm Section H3x1,5cm

**Ambient temperature range:** -10 / +35°C

**Materials:**  
body: extruded aluminum  
cover: pmma OPAL


**Weight:** 6 kg



**Leggera inclined ceiling Ø45cm+Ø65cm**  
designed by TI Lighting LAB

Inclined ceiling lamp with dimensions  
Ø45cm + Ø65cm in painted aluminum.  
DOWNLIGHT emission.


■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



3032ACOF

OPTIONS

DIMMABLE DALI (Push)

Code:  3032ACDM

PHASE CUT

Code: 3032ACTF

STRUCTURE FINISHES


- BV white
- RV painted copper
- BR painted bronze
- OV painted gold



**Leggera inclined ceiling Ø45cm+Ø65cm**  
designed by TI Lighting LAB

Inclined ceiling lamp with dimensions  
Ø45cm + Ø65cm in painted aluminum.  
DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

